

DC WATERPROOF TRANSFORMER



High-quality aluminum alloy shell, full glue-filled waterproof process

Waterproof level: IP67-P68

Wide working environment temperature range: -40°C-75°C

With multiple protections such as overload, overvoltage, overtemperature, short circuit, etc.

CE CB RoHS IP67 IP68



15 W



36 W



60 W



100 W



200 W



300 W



400 W



500 W



600 W

Product Code	001215	001236	001260	0012100	0012200	0012300
Power	15W	36W	60W	100W	200W	300W
Input	100-265V	100-265V	170-265V	170-265V	170-265V	170-265V
Output	24V 0.25A 12V 1.25A	24V 1.50A 12V 3.0A	24V 2.50A 12V 5.0A	24V 4.16A 12V 5.33A	24V 8.33A 12V 16.66A	24V 12.5A 12V 25.0A
Efficiency	≥90%	≥90%	≥90%	≥90%	≥90%	≥90%
Size	105*30*19mm	125*32*33mm	152*36*22mm	195*60*25mm	235*72*35mm	255*72*35mm

Product Code	0012400	0012500	0012600
Power	400W	500W	600W
Input	170-265V	170-265V	170-265V
Output	24V 16.66A 12V 33.33A	24V 20.83A 12V 41.66A	24V 25.0A 12V 50.0A
Efficiency	≥90%	≥90%	≥90%
Size	275*32*35mm	275*75*35mm	270*78*35mm