



**EPL-F0012**



- CHARACTERISTIC:** Protection class IP 68 10m
- SURFACE MATERIAL:** SUS 304 Stainless steel
- LAMP BODY:** SUS 304 Stainless steel
- LIGHT WINDOW:** Ultra white transparent tempered glass
- CABLE GLAND:** IP67 copper and nicked coated
- GASKET:** Molding shaped silicone seal
- RECESSED SLEEVE:** ABS Black Plastic
- LED DRIVER:** Constant Voltage input, Constant Current Output
- Ta:** -20°-40°
- POWER CABLE:** Chlorine water-resistant cable  
H07RN-F2x1mm<sup>2</sup>, L=1m, 3m, 5m (12V/24V)  
H05RN-F2x1.0+3\*0.3mm<sup>2</sup>, L=3m (12V/24V-DMX512)  
H05RN-F4x0.75mm<sup>2</sup>, L=1m, 3m, 5m (12V/24V-Dali)
- LED:** SMD3535
- IP/IK:** IP68/IK09
- DIMMING SUPPORT:** Triac, 1.10V, Dali, RGBW external decoder  
RGBW DMX512 built-in program, PWM  
Available RGBW Dali built-in program Customized

| Model       | Power (Watt) | LED Qty(PCS) | LED-CCT    |
|-------------|--------------|--------------|------------|
| EPL-F012-W  | 12 W         | 12x1W=12W    | White      |
| EPL-F012-WW | 12 W         | 12x1W=12W    | Warm White |
| EPL-F012-BL | 12 W         | 12x1W=12W    | Blue       |
| EPL-F012-MR | 12 W         | 12x1W=12W    | RGB        |

**Lumens(LM)**

White=3290    Warm white=3580    RGB=1510

