




EPL-LRPN210-14W



- CHARACTERISTIC:** Protection class IP 68 10m
- SURFACE MATERIAL:** SUS 304 Stainless steel
- LAMP BODY:** SUS 304 Stainless steel
- LIGHT WINDOW:** Ultra white transparent tempered glass
- CABLE GLAND:** IP67 copper and nicked coated
- GASKET:** Molding shaped silicone seal
- RECESSED SLEEVE:** ABS Black Plastic
- LED DRIVER:** Constant Voltage input, Constant Current Output
- Ta:** -20°-40°
- POWER CABLE:** Chlorine water-resistant cable
H07RN-F2x1mm², L=1m, 3m, 5m (12V/24V)
H05RN-F2x1.0+3*0.3mm², L=3m (12V/24V-DMX512)
H05RN-F4x0.75mm², L=1m, 3m, 5m (12V/24V-Dali)
- LED:** SMD3535
- IP/IK:** IP68/IK09
- DIMMING SUPPORT:** Triac, 1.10V, Dali, RGBW external decoder
RGBW DMX512 built-in program, PWM
Available RGBW Dali built-in program Customized

Model	Power (Watt)	LED Qty(PCS)
EPL-LRPN210-14W	14 W	14x1W=14W

Lumens(LM)

White=1540 Warm white=1750 RGB=770

