





**EPL-LRPN240-18W**



- CHARACTERISTIC:** Protection class IP 68 10m
- SURFACE MATERIAL:** SUS 304 Stainless steel
- LAMP BODY:** SUS 304 Stainless steel
- LIGHT WINDOW:** Ultra white transparent tempered glass
- CABLE GLAND:** IP67 copper and nicked coated
- GASKET:** Molding shaped silicone seal
- RECESSED SLEEVE:** ABS Black Plastic
- LED DRIVER:** Constant Voltage input, Constant Current Output
- Ta:** -20°-40°
- POWER CABLE:** Chlorine water-resistant cable  
H07RN-F2x1mm<sup>2</sup>, L=1m, 3m, 5m (12V/24V)  
H05RN-F2x1.0+3\*0.3mm<sup>2</sup>, L=3m (12V/24V-DMX512)  
H05RN-F4x0.75mm<sup>2</sup>, L=1m, 3m, 5m (12V/24V-Dali)
- LED:** SMD3535
- IP/IK:** IP68/IK09
- DIMMING SUPPORT:** Triac, 1.10V, Dali, RGBW external decoder  
RGBW DMX512 built-in program, PWM  
Available RGBW Dali built-in program Customized

| Model           | Power (Watt) | LED Qty(PCS) |
|-----------------|--------------|--------------|
| EPL-LRPN240-18W | 18 W         | 12x1W=18W    |

| Lumens(LM) |                 |         |
|------------|-----------------|---------|
| White=1980 | Warm white=2250 | RGB=990 |



Triac  
Dali  
0-10V  
DMX512

**IP68**
**IK09**