




Accessories



Feature

Tank : voluble molding of fiber glass reinforced plastics corrosion resistant, good abrasion resistance and deforming-proof. Uniquely designed distribution make a stable and even water flow to improve drainage system. Easy to install, maintain free Outlet turbidity. <2FTU.



工作压力 Working pressure (kPa): 350

Model No	Code	Diameter D (mm)	Inlet/Outlet (inch)	Flow (m ³ /h)	Filtration area (m ²)	H1 (mm)	H2 (mm)	H3 (mm)	WS (kg)	Package (mm)	NW (kg)	GW (kg)
EPL-SS1600	PLS-36	1400	3"	56	1.25	850	950	1480	1480	550*550*650	14.1	18.1
EPL-SS1600	PLS-37	1600	3"	100	2.01	850	950	1680	2180	620*620*680	16.9	21.4
EPL-SS1800	PLS-38	1800	4"	125	2.54	750	1100	1890	3100	680*680*740	20.0	25.5
EPL-SS2000	PLS-39	2000	6"	153	3.14	890	1290	2120	4250	720*720*750	22.3	27.8
EPL-SS2300	PLS-40	2350	8"	186	4.12	930	1480	2400	6325	780*780*830	25.7	32.7
EPL-SS2500	PLS-41	2500	8"	238	4.88	1030	1530	2740	7645	820*820*860	38.8	36.2