



SPF-48000

PRODUCT FEATURE

1. Adopting stainless ceramic shaft, the pump endures fray and rust and can be used in freshwater and seawater.
2. The motor is coated with resin, and the waterproof and isolation performance is excellent.
3. Multifunctional design——pumping, filtering and fountain 3 in 1.

APPLICATION

Be suitable for pumping and circulating the water in aquariums and seafood pools, filtering and cleaning the breeding water, and spraying the indoor and outdoor fountains.

Model	Voltage	Frequency	Power	H-Max	Output	Weight	Dimensions
HQB-2000	110V/220V/240V	50Hz/60Hz	24W	1.8m	1400L/h	0.8kg	138×65×145mm
HQB-2500	110V/220V/240V	50Hz/60Hz	55W	2.5m	2000L/h	1.2kg	153×105×135mm
HQB-3500	110V/220V/240V	50Hz/60Hz	85W	3.5m	3000L/h	1.25kg	153×105×135mm
HQB-4500	110V/220V/240V	50Hz/60Hz	100W	4.5m	4500L/h	2.7kg	175×112×133mm
HQB-5000	110V/220V/240V	50Hz/60Hz	150W	5.0m	5500L/h	2.8kg	175×112×133mm
HQB-5500	110V/220V/240V	50Hz/60Hz	200W	5.5m	6800L/h	3.5kg	200×140×160mm
JAP-7500	110V/220V/240V	50Hz/60Hz	170W	5.0m	7500L/h	3.5Kg	355×125×145mm
JAP-10000	110V/220V/240V	50Hz/60Hz	230W	6.0m	10000L/h	5.0Kg	375×130×153mm
JAP-13000/L	110V/220V/240V	50Hz/60Hz	420W	7.5m	13000L/h	5.0Kg	400×140×165mm
JAP-15000/L	110V/220V/240V	50Hz/60Hz	420W	7.0m	15000L/h	5.0Kg	400×140×165mm
JAP-18000/L	110V/220V/240V	50Hz/60Hz	420W	6.5m	18000L/h	5.0Kg	400×140×165mm
SPF-48000	220V/240V/380V	50Hz/60Hz	970W	8.0m	30000L/h	10.50Kg	415×170×206mm